



US009044297B2

(12) **United States Patent**
Rajkondawar et al.

(10) **Patent No.:** **US 9,044,297 B2**
(45) **Date of Patent:** **Jun. 2, 2015**

(54) **SYSTEM AND METHOD FOR ESTRUS
DETECTION USING REAL-TIME LOCATION**

(75) Inventors: **Parimal G. Rajkondawar**, Madison, WI
(US); **Roger K. Erdman**, Janesville, WI
(US); **David A. Johnson**, McFarland, WI
(US); **William S. Nelson**, Sun Prairie,
WI (US); **Paul D. Thompson**, Madison,
WI (US)

(73) Assignee: **Technologies Holdings Corp.**, Houston,
TX (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 826 days.

(21) Appl. No.: **13/050,053**

(22) Filed: **Mar. 17, 2011**

(65) **Prior Publication Data**

US 2012/0238912 A1 Sep. 20, 2012

(51) **Int. Cl.**

A61D 17/00 (2006.01)
A01K 29/00 (2006.01)
A61B 5/103 (2006.01)
A61B 5/00 (2006.01)
A01K 11/00 (2006.01)

(52) **U.S. Cl.**

CPC **A61D 17/002** (2013.01); **A61B 5/0002**
(2013.01); **A01K 11/006** (2013.01); **A01K**
29/005 (2013.01)

(58) **Field of Classification Search**

CPC **A61B 10/0012**
USPC 600/551, 588, 304, 30, 595; 119/174
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,206,766 A * 6/1980 Bielka 600/551
4,467,814 A * 8/1984 Preti 600/549

4,618,861 A * 10/1986 Gettens et al. 340/10.41
4,865,044 A * 9/1989 Wallace et al. 600/549
5,111,799 A * 5/1992 Senger et al. 600/551
5,322,034 A * 6/1994 Willham et al. 340/10.41
5,542,431 A * 8/1996 Starzl et al. 600/551
5,566,679 A * 10/1996 Herriott 600/551
5,857,434 A * 1/1999 Andersson 119/859
6,925,417 B2 * 8/2005 Sasaguri 702/183
6,997,140 B2 * 2/2006 Finlayson 119/858
7,020,508 B2 * 3/2006 Stivorice et al. 600/390

(Continued)

FOREIGN PATENT DOCUMENTS

FR 2 759 541 A1 8/1998 A61D 17/00
WO WO2008/113566 A1 * 9/2008

OTHER PUBLICATIONS

English Machine Translation of FR2759541, Oudet Patrick et al.,
Demande De Brevet D'Invention, Institute National De La Propriete
Industrielle, pp. 1-7.*

(Continued)

Primary Examiner — Brian Szmal

Assistant Examiner — Matthew Kremer


(74) *Attorney, Agent, or Firm* — Baker Botts L.L.P.

(57)

ABSTRACT

In certain embodiments, a method for estrus detection includes storing location information associated with a dairy livestock. The stored location information includes a coordinate location of the dairy livestock within a free stall pen at each of a plurality of times during a time period. The method further includes determining, based on at least a portion of the stored location information, one or more movement parameters associated with the dairy livestock. The method further includes determining, based on one or more movement parameters associated with the dairy livestock, whether the dairy livestock is likely to be in estrus.

17 Claims, 3 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

7,083,575 B1 * 8/2006 Claycomb et al. 600/551
 7,137,359 B1 * 11/2006 Braden 119/854
 7,234,421 B2 * 6/2007 Natividade et al. 119/720
 7,610,879 B2 * 11/2009 Gardner et al. 119/720
 7,670,292 B2 * 3/2010 Haynes 600/443
 7,785,267 B2 * 8/2010 Francke et al. 600/551
 7,927,287 B2 * 4/2011 Anderson et al. 600/551
 8,307,785 B2 * 11/2012 Zimmerman et al. 119/51.02
 2002/0156394 A1 * 10/2002 Mehrotra et al. 600/551
 2003/0224452 A1 * 12/2003 Colgin et al. 435/7.1
 2007/0032733 A1 * 2/2007 Burton 600/509

2008/0110405 A1 * 5/2008 Voronin et al. 119/174
 2008/0110406 A1 * 5/2008 Anderson et al. 119/174
 2008/0314325 A1 * 12/2008 Hempstead et al. 119/51.02
 2010/0030036 A1 2/2010 Mottram et al. 600/301
 2010/0107985 A1 5/2010 O'Hare 119/174

OTHER PUBLICATIONS

PCT Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US2012/026234; 12 pages, May 31, 2012.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3

1

SYSTEM AND METHOD FOR ESTRUS DETECTION USING REAL-TIME LOCATION

TECHNICAL FIELD

This invention relates generally to dairy farming and more particularly to a system and method for estrus detection using real-time location.

BACKGROUND OF THE INVENTION

For modern dairy milking operations to remain profitable, it may be important to maximize the efficiency of a herd of dairy livestock. In order to maximize efficiency of a herd of dairy livestock, it may be beneficial to ensure that the livestock remain healthy and have a high reproductive efficiency. Accordingly, health monitoring and estrus detection for a herd of dairy livestock may be integral components of modern dairy milking operations. Current systems and methods supporting health monitoring and estrus detection, however, have proven inadequate in various respects.

SUMMARY OF THE INVENTION

According to embodiments of the present disclosure, disadvantages and problems associated with previous systems and methods for estrus detection may be reduced or eliminated.

In certain embodiments, a method for estrus detection includes storing location information associated with a dairy livestock. The stored location information includes a coordinate location of the dairy livestock within a free stall pen at each of a plurality of times during a time period. The method further includes determining, based on at least a portion of the stored location information, one or more movement parameters associated with the dairy livestock. The method further includes determining, based on one or more movement parameters associated with the dairy livestock, whether the dairy livestock is likely to be in estrus.

Particular embodiments of the present disclosure may provide one or more technical advantages. For example, certain embodiments of the present disclosure may increase the reproductive efficiency for a herd of dairy livestock by facilitating an automated determination regarding whether each of the dairy livestock is in estrus based on the movement of the dairy livestock within a free stall pen. Moreover, a high reproductive efficiency within a herd of dairy livestock may increase the overall milk output for that herd over a period of time. As a result, certain embodiments of the present disclosure may facilitate an increase in the overall milk output for a herd of dairy livestock.

Certain embodiments of the present disclosure may include some, all, or none of the above advantages. One or more other technical advantages may be readily apparent to those skilled in the art from the figures, descriptions, and claims included herein.

BRIEF DESCRIPTION OF THE DRAWINGS

To provide a more complete understanding of the present invention and the features and advantages thereof, reference is made to the following description taken in conjunction with the accompanying drawings, in which:

FIG. 1 illustrates a logical view of an example system for estrus detection and health monitoring using real-time location, according to certain embodiments of the present disclosure; and

2

FIG. 2 illustrates an example method for estrus detection using real-time location, according to certain embodiments of the present disclosure; and

FIG. 3 illustrates an example method for health monitoring using real-time location, according to certain embodiments of the present disclosure.

DETAILED DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a logical view of an example system **100** for estrus detection and health monitoring using real-time location, according to certain embodiments of the present disclosure. System **100** includes a free stall pen **102** housing a number of dairy livestock **104**. Free stall pen **102** may be configured to include a number of stalls **106**, walking lanes **108**, and water troughs **110**, and may be positioned adjacent to a feed lane **112**. System **100** further includes a number of identification devices **114** positioned throughout free stall pen **102**, each identification device **114** being configured to (1) read tags affixed to each of the dairy livestock **104**, and (2) communicate with a controller **116**. Although this particular implementation of system **100** is illustrated and primarily described, the present disclosure contemplates any suitable implementation of system **100** according to particular needs. Additionally, although the present disclosure contemplates free stall pen **102** housing any suitable dairy livestock **104** (e.g., cows, goats, sheep, water buffalo, etc.), the remainder of this description is detailed with respect to dairy cows.

Free stall pen **102** may include any suitable number of walls dividing free stall pen **102** into a number of stalls **106** and a number walking lanes **108**. The walls of free stall pen **102** may be constructed of any suitable materials arranged in any suitable configuration operable to manage the movement of dairy cows **104**. For example, the walls of free stall pen **102** may each include any number and combination of posts, rails, tubing, rods, connectors, cables, wires, and/or beams operable to form a substantially planar barricade such as a fence, wall, and/or other appropriate structure suitable to manage the movement of dairy cows **104**. Free stall pen **102** may additionally include a number of water troughs **110** each positioned at any suitable location within free stall pen **102** such that dairy cows **104** may access drinking water.

Free stall pen **102** may be positioned adjacent to a feed lane **112**. Feed lane **112** may be configured to permit a vehicle to pass through feed lane **112** and distribute feed for dairy cows **104** located in free stall pen **102**. For example, feed lane **112** may be separated from free stall pen **102** by a wall comprising a number of slots sized such that dairy cows **104** may extend their heads into feed lane **112** and eat feed distributed in feed lane **112**.

A number of identification devices **114** may be positioned at various locations within and/or adjacent to free stall pen **102**. Although a particular number of identification devices **114** are illustrated as being positioned at particular locations within free stall pen **102**, the present disclosure contemplates any suitable number of identification devices **114** located at any suitable positions within and/or adjacent to free stall pen **102**, according to particular needs.

Identification devices **114** may each include any suitable device operable to receive a signal from a tag affixed to a dairy cow **104** (e.g., an ear tag) located in free stall pen **102**. In response to a signal received from a tag affixed to a dairy cow **104**, identification devices **114** may generate a signal corresponding to that tag for communication to controller **116** (described below). Communication between identification devices **114** and tags affixed to dairy cows **104** may be facilitated by any suitable technology, including, for example,

passive radio-frequency identification (RFID), active RFID, Wi-Fi, Bluetooth, ultra-wide band (UWB), ZigBee, acoustic locating, and computer vision. In certain embodiments, a generated signal corresponding to a tag affixed to a dairy cow **104** may include (1) an identification number related to the dairy cow **104**, (2) the distance, angle, and/or other information concerning the location of the dairy cow **104** relative to the identification device **114** generating the signal, (3) an identification of the identification device **114** generating the signal, and/or (4) a timestamp.

Identification devices **114** may be communicatively coupled (e.g., via a network facilitating wireless or wireline communication) to controller **116**. Controller **116** may include one or more computer systems at one or more locations. Each computer system may include any appropriate input devices (such as a keypad, touch screen, mouse, or other device that can accept information), output devices, mass storage media, or other suitable components for receiving, processing, storing, and communicating data. Both the input devices and output devices may include fixed or removable storage media such as a magnetic computer disk, CD-ROM, or other suitable media to both receive input from and provide output to a user. Each computer system may include a personal computer, workstation, network computer, kiosk, wireless data port, personal data assistant (PDA), one or more processors within these or other devices, or any other suitable processing device. In short, controller **116** may include any suitable combination of software, firmware, and hardware.

Controller **116** may additionally include one or more processing modules **118** and one or more memory modules **120** (each referred to in the singular throughout the remainder of this description). Processing module **118** may include one or more microprocessors, controllers, or any other suitable computing devices or resources and may work, either alone or with other components of system **100**, to provide a portion or all of the functionality of system **100** described herein. Memory module **120** may take the form of volatile or non-volatile memory including, without limitation, magnetic media, optical media, random access memory (RAM), read-only memory (ROM), removable media, or any other suitable memory component.

Controller **116** may additionally include real-time location (RTL) logic **122**, estrus detection logic **124**, and health monitoring logic **126** (e.g., each stored memory module **120**). RTL logic **122** (which, in combination with identification devices **114** and the plurality of tags affixed to the plurality of dairy cows **104**, may be referred to as a real-time location system (RTLS)) may include any information, logic, and/or instructions stored and/or executed by controller **116** to determine location information **128** associated with dairy cows **104** in free stall pen **102** based on signals received from identification devices **114** (as described in further detail below). Estrus detection logic **124** may include any information, logic, and/or instructions stored and/or executed by controller **116** to determine, based on the location information **128** associated with a particular dairy cow **104** generated by RTL logic **122**, whether the particular dairy cow **104** is likely to be in estrus (as described in further detail below). Health monitoring logic **126** may include any information, logic, and/or instructions stored and/or executed by controller **116** to determine, based on the location information **128** associated with a particular dairy cow **104** generated by RTL logic **122**, whether the particular dairy cow **104** is likely unhealthy (as described in further detail below). Although certain functionality is described below as being associated with RTL logic **122**, estrus detection logic **124**, or health monitoring logic **126**, the present disclosure contemplates the functionality described

below as being combined or divided among any suitable logic, according to particular needs.

Controller **116** may be operable to receive signals generated by identification devices **114**. In certain embodiments, controller **116** may receive signals corresponding to each dairy cow **104** in free stall pen **102** from each identification device **114**. Furthermore, for a particular dairy cow **104**, controller **116** may receive signals from each identification device **114** at or about the same time and at regular intervals (e.g., every fifteen seconds). For example, for a particular dairy cow **104** at a particular time, controller **116** may receive signals generated by a number of identification devices **114** (e.g., each signal identifying the particular dairy cow **104** and the distance the particular dairy cow **104** is located from the corresponding identification device **114**). Based on the received signals, controller **116** may determine location information **128** associated with the particular dairy cow **104** at the particular time (e.g., using RTL logic **122**, as described below).

In certain embodiments, RTL logic **122** may be operable to process signals received from identification devices **114** in order to determine location information **128** associated with dairy cows **104** in free stall pen **102**. As described above, a particular subset of the received signals may be generated by the identification devices **114** at approximately the same time and may identify the same particular dairy cow **104**. Each of the signals of the particular subset may additionally include information about the position of the particular dairy cow **104** relative to the corresponding identification device **114** (e.g., distance, angle, etc.). Based on one or more of the subset of received signals, RTL logic **122** may determine a coordinate location of the particular dairy cow **104** within free stall pen **102**. In certain embodiments, the determined coordinate location may be an (X,Y) location within the free stall pen **102**. In certain other embodiments, the determined coordinate location may be an (X,Y,Z) location within the free stall pen **102**.

As just one example, RTL logic **122** may determine a coordinate location of the particular dairy cow **104** within free stall pen **102** using triangulation (based on at least three of the subset of received signals). Because each of the at least three signals may include information about the position of the particular dairy cow **104** (e.g., distance and/or angle) relative to the corresponding identification device **114** and the location of each corresponding identification device **114** within free stall pen **102** may be known, the coordinate location (e.g., an (X,Y) location, an (X,Y,Z) location, or any other suitable coordinate location) of the particular dairy cow **104** within free stall pen **102** may be determined.

Furthermore, because controller **116** may receive signals from identification devices **114** for each dairy cow **104** on a periodic basis (e.g., every fifteen seconds), location information **128** may be generated for each dairy cow **104** in free stall pen **102** at each of a number of times during a particular time period (e.g., every fifteen seconds over a one hour period). The generated location information **128** associated with each dairy cow **104** may then be stored (e.g., in memory module **120** or any other suitable location in system **100**) such that the location information **128** may be later accessed (e.g., by estrus detection logic **124** and health monitoring logic **126**, as described in further detail below).

In certain embodiments, estrus detection logic **124** may be operable to access location information **128** associated with each dairy cow **104** in free stall pen **102** and determine, based on at least a portion of that location information **128**, one or more movement parameters **130** associated with each dairy cow **104**. The determined movement parameters **130** for dairy cows **104** may be stored (e.g., in memory module **120**) such

5

that changes in the movement parameters 130 may be assessed over time. Because the movement of a dairy cow 104 within free stall pen 102 (as reflected by the movement parameters 130, which are described in detail below) may be indicative of whether the dairy cow 104 is in estrus, the movement parameters 130 may be used by estrus detection logic 124 to determine whether the dairy cow 104 is likely to be in estrus (as described below).

In certain embodiments, the movement parameters 130 for a particular dairy cow 104 may include a percentage of a particular time period (e.g., one hour) the particular dairy cow 104 spent in each of a number of areas of free stall pen 102. For example, the movement parameters 130 may include (1) a percentage of time the particular dairy cow 104 spent standing in a stall 106 of free stall pen 102 (stall standing parameter 134), (2) a percentage of time the particular dairy cow 104 spent lying in a stall 106 of free stall pen 102 (stall lying parameter 136), (3) a percentage of time the particular dairy cow 104 spent walking in a walking alley 108 of free stall pen 102 (alley walking parameter 138), (4) a percentage of time the particular dairy cow 104 spent lying in a walking alley 108 of free stall pen 102 (alley lying parameter 140), (5) a percentage of time the particular dairy cow 104 spent standing in a walking alley 108 of free stall pen 102 (alley standing parameter 142) (6) a percentage of time the particular dairy cow 104 spent near a water trough 110 (watering parameter 144), and/or (7) a percentage of time the particular dairy cow 104 spent near feed lane 112 (feeding parameter 146).

The above-described movement parameters 130 for a particular dairy cow 104 may be determined by comparing the location information 128 for the particular dairy cow 104 collected during a particular time period (including a number of coordinate locations for the particular dairy cow 104 at a number of discrete times during the particular time period, as described above) with layout information 132 for free stall pen 102 (e.g., stored in memory module 120). In certain embodiments, layout information 132 for free stall pen 102 may include coordinate locations defining the corners of each stall 106 (and thus defining the area within each stall 106), coordinate locations defining the corners of each walking lane 108 (and thus defining the area within each walking lane 108), coordinate locations defining the corners of the area around each water trough 110 (and thus defining a watering area), and the corners of the area near feed lane 112 (and thus defining a feeding area). For each coordinate location for the particular dairy cow 104 within these defined areas, the area in which the particular dairy cow 104 is located at each discrete time during the time period may be determined.

For example, location information 128 for a particular dairy cow 104 may include coordinate locations of the particular dairy cow 104 at discrete times (e.g., every fifteen seconds) during a particular time period (e.g., one hour). By comparing each (X,Y) coordinate location of the particular dairy cow 104 with layout information 132 for free stall pen 102, the position of the particular dairy cow 104 within free stall pen 102 may be determined at each discrete time during the time period. Moreover, if it is assumed that the position of the particular dairy cow 104 remains constant from one discrete time to the next (e.g., for the fifteen second time period until a new coordinate location for the particular dairy cow 104 is available), a percentage of the particular time period that the particular dairy cow 104 spent in various locations within the free stall pen 102 may be determined. Furthermore, in embodiments in which the coordinate location for the particular dairy cow 104 includes a (Z) location, a percentage of the particular time period that the particular dairy cow 104 spent standing versus lying at each location may additionally

6

be determined (as a (Z) location for the particular dairy cow 104 in both a standing and lying position may be known). From this information, the above-described movement parameters 130 (e.g., a stall standing parameter 134, a stall lying parameter 136, an alley walking parameter 138, an alley lying parameter 140, an alley standing parameter 142, a watering parameter 144, and a feeding parameter 146) may be determined.

In certain embodiments, the movement parameters 130 for a particular dairy cow 104 may additionally include a watering count 148 and a feeding count 150. The watering count 148 may correspond to the number of times during a time period that the particular dairy cow 104 moves within a predetermined distance (e.g., five feet) of a water trough 110. Similarly, the feeding count 150 may correspond to the number of times during a time period that the particular dairy cow 104 moves within a predetermined distance (e.g., five feet) of feed lane 112. Additionally, in embodiments in which location information 128 includes a (Z) coordinate location, movement parameters 130 for a particular dairy cow 104 may additionally include a mounting count 152. The mounting count 152 may correspond to the number of times during a particular time period that the (Z) coordinate location of the particular dairy cow 104 increasing above a particular threshold (indicating that the particular dairy cow 104 has mounted another dairy cow 104).

In certain embodiments, the movement parameters 130 for a particular dairy cow 104 may additionally include a mobility count 154. The mobility count 154 may correspond to the number of times during a time period that the particular dairy cow 104 moves more than a predetermined distance (e.g., five feet) between consecutive discrete times for which a coordinate location is available for the particular dairy cow 104 (e.g., during the fifteen second interval between times that identification devices 114 generate signals corresponding to the particular dairy cow 104). As just one example, in embodiments in which the location information 128 for the particular dairy cow 104 includes (X,Y) location for the particular dairy cow 104 at a number of discrete times (t), the mobility count 154 may be determined as follows:

If

$$[X(t+1)-X(t)]>5 \text{ feet}$$

or

$$[Y(t+1)-Y(t)]>5 \text{ feet}$$

then increase mobility count by 1

In certain embodiments, the mobility count 154 may be normalized to determine a mobility count per hour by dividing the determined mobility count 154 by the number of hours in the time period during which the mobility count 154 was determined.

In certain embodiments, the movement parameters 130 for a particular dairy cow 104 may additionally include a distance traveled 156 by the particular dairy cow 104 during a time period. As just one example, in embodiments in which the location information 128 for the particular dairy cow 104 includes (X,Y) location for the particular dairy cow 104 at a number of discrete times (t), the distance traveled 156 by the particular dairy cow 104 may be determined as follows:

$$Dist.Trav. = \sum_{t=1}^n \sqrt{(X(t+1) - X(t))^2 + (Y(t+1) - Y(t))^2}$$

7

In certain embodiments, the distance traveled **156** by the particular dairy cow **104** in a time period may be normalized to determine a distance traveled per hour by dividing the determined distance traveled **156** by the number of hours in the time period for which the distance traveled **156** was determined.

In certain embodiments, the movement parameters **130** for a particular dairy cow **104** may additionally include a turn count **158**. The turn count **158** may correspond to the number of times during a time period that the particular dairy cow **104** changes direction between consecutive discrete times for which a coordinate location is available for the particular dairy cow **104** (e.g., the difference in angular direction of the particular dairy cow **104** from discrete time to the next changes less than 90° or more than 270°). As just one example, in embodiments in which the location information for the particular dairy cow **104** includes (X,Y) location for the particular dairy cow **104** at a number of discrete times (t), the turn count **158** for the particular dairy cow **104** may be determined as follows:

If

$$\text{angle} < 90^\circ$$

or

$$\text{angle} > 270^\circ$$

then increase turn count by 1
where:

$$\text{angle} = \arccos\left[\frac{c^2 - b^2 - a^2}{2ba}\right]$$

$$a = \sqrt{(Y(t+1) - Y(t))^2 + (X(t+1) - X(t))^2}$$

$$b = \sqrt{(Y(t+2) - Y(t+1))^2 + (X(t+2) - X(t+1))^2}$$

$$c = \sqrt{(Y(t+2) - Y(t))^2 + (X(t+2) - X(t))^2}$$

In certain embodiments, the turn count **158** may be normalized to determine a number of turns per hour by dividing the determined turn count **158** by the number of hours in the time period for which the turn count **158** was determined.

In certain embodiments, the movement parameters **130** for a particular dairy cow **104** may additionally include a sign change count **160**. Like the turn count **158**, the sign change count **160** may correspond to the number of times during a time period that the particular dairy cow **104** changes direction between consecutive discrete times for which a coordinate location is available for the particular dairy cow **104**. As just one example, in embodiments in which the location information for the particular dairy cow **104** includes (X,Y) location for the particular dairy cow **104** at a number of discrete times (t), the sign change count **160** for the particular dairy cow **104** may be determined as follows:

If

$$[X(t+1) - X(t)] > 0 \text{ and } [X(t+2) - X(t+1)] < 0 \text{ (or vice versa)}$$

or

$$[Y(t+1) - Y(t)] > 0 \text{ and } [Y(t+2) - Y(t+1)] < 0 \text{ (or vice versa)}$$

then increase sign change count by 1

In certain embodiments, the sign change count **160** may be normalized to determine a number of sign changes per hour

8

by dividing the determined sign change count **160** by the number of hours in the time period for which the sign change count **160** was determined.

Estrus detection logic **124** may additionally be operable to determine, based on one or more of the above-described movement parameters **130** associated with dairy cows **104** (determined based on coordinate locations for the particular dairy cow **104** during a particular time period, as described above), which of the dairy cows **104** are likely to be in estrus at a given time.

For example, estrus detection logic **124** may determine if a particular dairy cow **104** is likely to be in estrus by comparing a “heat index” for the particular dairy cow **104** (described below) with a baseline heat index. In certain embodiments, the heat index for a particular dairy cow **104** may correspond to the product of an alley walking parameter **138** and a normalized mobility count **154** (e.g., heat index = (alley walking parameter) × (mobility count/hour)). In such embodiments, the heat index may be indicative of the amount of movement of the particular dairy cow **104**, with a certain amount of increase in movement of the particular dairy cow **104** (e.g., 250% over a baseline, as described below) being an indicator that the particular dairy cow **104** is in estrus.

In certain other embodiments, the heat index for a particular dairy cow **104** may correspond to a function of stall standing parameter **134**, stall lying parameter **136**, alley walking parameter **138**, alley lying parameter **140**, ally standing parameter **142**, watering parameter **144**, feeding parameter **146**, watering count **148**, feeding count **150**, mounting count **152**, mobility count **154**, distance traveled **156**, turn count **158**, and/or sign change count **160**. As just one example, the heat index may be calculated as follows:

Heat Index =

$$a^* (\text{stall standing parameter } 134) + b^* (\text{stall lying parameter } 136) +$$

$$c^* (\text{alley walking parameter } 138) + d^* (\text{alley lying parameter } 140) +$$

$$e^* (\text{ally standing parameter } 142) + f^* (\text{watering parameter } 144) +$$

$$g^* (\text{feeding parameter } 146) + h^* (\text{watering count } 148) +$$

$$i^* (\text{feeding count } 150) + j^* (\text{mounting count } 152) +$$

$$k^* (\text{mobility count } 154) + l^* (\text{distance traveled } 156) +$$

$$m^* (\text{turn count } 158) + n^* (\text{sign change count } 160)$$

where:

$$a = -10$$

$$b = -10$$

$$c = 35$$

$$d = -10$$

$$e = -10$$

$$f = 0$$

$$g = -20$$

$$h = 10$$

$$i = -10$$

$$j = 20$$

$$k = 30$$

$$l = 40$$

$$m = 20$$

$$n = 15$$

In such embodiments, the heat index may be indicative of an increase in certain activity of the particular dairy cow **104** (e.g., walking in walking lanes **108**, pacing, and/or mounting other dairy cows **104**), with an increase in such activity being

an indicator that the particular dairy cow **104** is in estrus. Although particular constants a-n are listed as being used to calculate the heat index for example purposes, the present disclosure contemplates any suitable constants, according to particular needs.

If the heat index for particular dairy cow **104** is greater than the baseline heat index by more than a predefined amount (e.g., 250%), estrus detection logic **124** may determine that the particular dairy cow **104** is likely to be in estrus (as such an increase may indicate either that (1) the amount of movement of the particular dairy cow **104** has increased or (2) the particular dairy cow **104** is spending time in those portions of the free stall pen **102** in which a dairy cow **104** likely to be in estrus is likely to be located, such as walking lanes **108**). The baseline heat index may be (1) a heat index for the particular dairy cow **104** during a previous time period (e.g., the previous twenty-four hours), (2) an average heat index for one or more other dairy cows **104** in free stall pen **102** during a previous time period (e.g., the previous twenty-four hours), (3) a user defined baseline heat index, or (4) any other suitable baseline heat index, according to particular needs. In certain embodiments, the baseline heat index may take into account the ambient conditions in the free stall pen **102** (e.g., temperature), as the movement of dairy cows **104** within free stall pen **102** may vary based on those conditions.

As another example, estrus detection logic **124** may compare a distance traveled **156** by the particular dairy cow **104** (e.g., a distance traveled per hour during a particular time period, as described above) with a baseline distance traveled. If the distance traveled **156** by the particular dairy cow **104** is greater than the baseline distance traveled by more than a predefined amount (e.g., 250%), estrus detection logic **124** may determine that the particular dairy cow **104** is likely to be in estrus (as an increase in movement of the particular dairy cow **104** may be an indicator that the particular dairy cow **104** is in estrus). The baseline distance traveled may be (1) a distance traveled by the particular dairy cow **104** during a previous time period (e.g., the distance traveled per hour during the previous twenty-four hours), (2) an average distance traveled by one or more other dairy cows **104** in free stall pen **102** during a previous time period (e.g., the average distance traveled per hour during the previous twenty-four hours), (3) a user defined baseline distance traveled, or (4) any other suitable baseline distance traveled, according to particular needs. In certain embodiments, the baseline distance traveled may take into account the ambient conditions in the free stall pen **102** (e.g., temperature), as the movement of dairy cows **104** within free stall pen **102** may vary based on those conditions.

As yet another example, estrus detection logic **124** may compare a "turn index" for a particular dairy cow **104** (described below) with a baseline turn index. In certain embodiments, the turn index may correspond to the sum of turn count **158** and sign change count **160** (e.g., $\text{turn index} = (\text{turn count}) + (\text{sign change count})$). In such embodiments, the turn index may be indicative of pacing by the particular dairy cow **104**, which may be an indicator that the particular dairy cow **104** is in estrus.

If the turn index for particular dairy cow **104** is greater than the baseline turn index by more than a predefined amount (e.g., 250%), estrus detection logic **124** may determine that the particular dairy cow **104** is likely to be in estrus (as such an increase may be indicative of an increase in pacing by the particular dairy cow **104**, which may be indicative of estrus). The baseline turn index may be (1) a turn index for the particular dairy cow **104** during a previous time period (e.g., the previous twenty-four hours), (2) an average turn index for

one or more other dairy cows **104** in free stall pen **102** during a previous time period (e.g., the previous twenty-four hours), (3) a user defined baseline turn index, or (4) any other suitable baseline turn index, according to particular needs. In certain embodiments, the baseline turn index may take into account the ambient conditions in the free stall pen **102** (e.g., temperature), as the movement of dairy cows **104** within free stall pen **102** may vary based on those conditions.

Having determined that a particular dairy cow **104** is likely to be in estrus, estrus detection logic **124** may be further operable to confirm that determination. For example, in response to a determination that a particular dairy cow **104** is likely to be in estrus, estrus detection logic **124** may access stored information associated with the particular dairy cow **104** (e.g., stored in memory module **120**) to determine if the particular dairy cow **104** is near the twenty-first day of her cycle. A determination that the particular dairy cow **104** is near the twenty-first day of her cycle may provide further confirmation that the particular dairy cow **104** is likely to be in estrus.

As an additional example, in response to a determination that a particular dairy cow **104** is likely to be in estrus, estrus detection logic **124** may initiate the generation of a signal to be communicated to identification devices **114**, the signal causing identification devices **114** to increase the frequency with which the tag of the particular dairy cow **104** is read (e.g., from fifteen seconds to five seconds). As a result, updated location information **128** may be generated by RTL logic **122** (including coordinate locations for the particular dairy cow **104** at more closely spaced intervals). Based on that updated location information **128**, one or more of the above-described movement parameters **130** may be recalculated, and estrus detection logic **124** may make a subsequent determination regarding whether the particular dairy cow **104** is likely to be in estrus (in a manner substantially similar to that described above) in order to further confirm the original estrus determination. In certain embodiments, the frequency with which the tag of the particular dairy cow **104** is read may revert to the default frequency (e.g., fifteen seconds) in response to the expiration of a predetermined period of time (e.g., one hour), in response to user input, or in response to any other suitable trigger.

As yet another example, in response to a determination that a particular dairy cow **104** is likely to be in estrus, estrus detection logic **124** may access location information **128** for other dairy cows **104** in free stall pen **102** to identify those other dairy cows **104** within a predefined distance of the particular dairy cow **104**. Estrus detection logic **124** may monitor location information **128** of the identified other dairy cows **104** to determine if there are any increases in the (Z) coordinate location for the identified other dairy cows **104**. An increase in the (Z) coordinate location of another dairy cow **104** located near the particular dairy cow **104** may indicate that the other dairy cow **104** is mounting the particular dairy cow **104**, which may provide further confirmation that the particular dairy cow **104** is in estrus.

As yet another example, in response to a determination that a particular dairy cow **104** is in estrus, estrus detection logic **124** may access location information **128** for other dairy cows **104** in free stall pen **102** to identify those other dairy cows **104** within a predefined distance of the particular dairy cow **104**. Estrus detection logic **124** may then monitor the location of the identified other dairy cows **104** to determine if any remain within a predefined distance of the particular dairy cow **104** for an extended period of time (e.g., one hour). Certain of the identified other dairy cows **104** remaining near the particular dairy cow **104** may indicate the presence of a sexually active

11

group (SAG) (i.e., a group of dairy cows **104** which are each in estrus). Determining that the particular dairy cow **104** is a member of a SAG may provide further confirmation that the particular dairy cow **104** is likely to be in estrus.

Having determined that one or more dairy cows **104** are likely to be in estrus (and possibly subsequent to confirming those determinations), estrus detection logic **124** may create exception reports to be stored in association with the one or more dairy cows **104** (e.g., in memory module **120**). Additionally or alternatively, estrus detection logic **124** may initiate the communication of reports (e.g., emails) to the farmer for each of the one or more dairy cows **104** such that the farmer may further monitor the one or more dairy cows **104** and/or remove the one or more dairy cows **104** from the free stall pen **102** for breeding. In certain embodiments, a report communicated to a farmer may indicate the relative strength of the estrus determination.

In certain embodiments, health monitoring logic **126** may be operable to access location information **128** associated with each dairy cow **104** in free stall pen **102** and determine, based on at least a portion of that location information, one or more movement parameters **130** associated with each dairy cow **104**. For example, health monitoring logic **126** may determine movement parameters **130** including a percentage of a particular time period (e.g., one hour) the dairy cows **104** spent in each of a number of areas of free stall pen **102**. For example, health monitoring logic **126** may determine a stall standing parameter **134**, a stall lying parameter **136**, an alley walking parameter **138**, an alley lying parameter **140**, an alley standing parameter **142**, a watering parameter **144**, a feeding parameter **146**, a watering count **148**, and/or a feeding count **150** in a manner substantially similar to that described above. The determined movement parameters **130** for dairy cows **104** may be stored (e.g., in memory module **120**) such that changes in the movement parameters **130** may be assessed over time. Because the movement of a dairy cow **104** within free stall pen **102** may be indicative of whether the dairy cow **104** is likely unhealthy, the movement parameters may be used by health monitoring logic **126** to determine if one or more dairy cows **104** are unhealthy (as described below).

Although health monitoring logic **126** and estrus detection logic **124** are each described as determining common movement parameters for dairy cows **104**, the present disclosure contemplates those parameters being calculated by health monitoring logic **126**, estrus detection logic **124**, or by any other suitable logic (e.g., RTL logic **122**) such that the movement parameters may be shared between health monitoring logic **126** and estrus detection logic **124**.

Health monitoring logic **126** may additionally be operable to determine, based on one or more of the above-described movement parameters **130** associated with dairy cows **104** (determined based coordinate locations for the particular dairy cow **104** during a particular time period, as described above), which of the dairy cows **104** are unhealthy at a given time. For example, health monitoring logic **126** may compare a "health index" for a particular dairy cow **104** (described below) with a baseline health index. In certain embodiments, the health index for the particular dairy cow **104** may correspond to a function of a stall standing parameter **134**, a stall lying parameter **136**, an alley walking parameter **138**, an alley lying parameter **140**, an alley standing parameter **142**, a watering parameter **144**, a feeding parameter **146**, a watering count

12

148, and/or a feeding count **150**. As just one example, the health index may be calculated as follows:

Health Index =

$$\begin{aligned} & a^*(\text{stall standing parameter } 134) + b^*(\text{stall lying parameter } 136) + \\ & c^*(\text{alley walking parameter } 138) + d^*(\text{alley lying parameter } 140) + \\ & e^*(\text{ally standing parameter } 142) + f^*(\text{watering parameter } 144) + \\ & g^*(\text{feeding parameter } 146) + h^*(\text{watering count } 148) + \\ & i^*(\text{feeding count } 150) + j^*(\text{mounting count } 152) + \\ & k^*(\text{mobility count } 154) + l^*(\text{distance traveled } 156) + \\ & m^*(\text{turn count } 158) + n^*(\text{sign change count } 160) \end{aligned}$$

where:

a=0
b=0
c=-20
d=20
e=0
f=0
g=-40
h=0
i=0
j=0
k=0
l=-30
m=0
n=0

In such embodiments, the health index may be indicative of an amount of time the particular dairy cow **104** spent in each of the various portions of free stall pen **102**, with an increase in activity in certain portions of free stall pen **102** (e.g., an increase in the amount of time spent lying in walking alleys **108**) being an indicator that the particular dairy cow **104** is unhealthy. Although particular constants a-n are listed as being used to calculate the health index for example purposes, the present disclosure contemplates any suitable constants, according to particular needs.

If the health index for particular dairy cow **104** is greater than the baseline health index by more than a predefined amount (e.g., 250%), health monitoring logic **126** may determine that the particular dairy cow **104** is likely unhealthy. The baseline health index may be (1) a health index for the particular dairy cow **104** during a previous time period (e.g., the previous twenty-four hours), (2) an average health index for one or more other dairy cows **104** in free stall pen **102** during a previous time period (e.g., the previous twenty-four hours), (3) a user defined baseline health index, or (4) any other suitable baseline health index, according to particular needs.

Having determined that a particular dairy cow **104** is likely unhealthy, health monitoring logic **126** may be operable to confirm that determination. For example, health monitoring logic **126** may initiate the generation of a signal to be communicated to identification devices **114**, the signal causing identification devices **114** to increase the frequency with which the tag of the particular dairy cow **104** is read (e.g., from fifteen seconds to five seconds). As a result, updated location information **128** may be generated by RTL logic **122** (including coordinate locations for the particular dairy cow **104** at more closely spaced intervals). Based on that updated location information **128**, one or more of the above-described movement parameters **130** may be recalculated, and health

13

monitoring logic 126 may make a subsequent determination regarding whether the particular dairy cow 104 is likely unhealthy (in a manner substantially similar to that described above) in order to further confirm the original unhealthy determination. In certain embodiments, the frequency with which the tag of the particular dairy cow 104 is read may revert to the default frequency (e.g., fifteen seconds) in response to the expiration of a predetermined period of time (e.g., one hour), in response to user input, or in response to any other suitable trigger.

Having determined that one or more dairy cows 104 are unhealthy (and possibly subsequent to confirming those determinations), health monitoring logic 126 may create exception reports to be stored in association with the one or more dairy cows 104 (e.g., in memory module 120). Additionally or alternatively, health monitoring logic 126 may initiate the communication of reports (e.g., emails) to the farmer for each of the one or more dairy cows 104 such that the farmer may further monitor the one or more dairy cows 104 and/or remove the one or more dairy cows 104 from the free stall pen 102 for medical attention. In certain embodiments, a report communicated to a farmer may indicate the relative strength of the determination that a dairy cow 104 is likely unhealthy.

Although a particular implementation of system 100 is illustrated and primarily described, the present disclosure contemplates any suitable implementation of system 100, according to particular needs.

FIG. 2 illustrates an example method 200 for estrus detection, according to certain embodiments of the present disclosure. Although method 200 is described with regard to a particular dairy cow 104, the present disclosure contemplates a substantially similar method being performed with regard to each of the plurality of dairy cows 104 in free stall pen 102.

The method begins at step 202. At step 204, controller 116 receives signals generated by a number of the identification devices 114 positioned at various locations in and/or around free stall pen 102. Each signal corresponds to a tag affixed to a particular dairy cow 104 located in a free stall pen 102 at one of a number of times during a time period. At step 206, controller 116 processes the received signals (e.g., using RTL logic 122, described above) to determine location information 128 associated with the particular dairy cow 104. The determined location information 128 may include a coordinate location of the dairy livestock within the free stall pen 102 at each of the number of times during the time period (e.g., every fifteen seconds during a one hour time period). For example, each of the received signals may include information about the distance from a corresponding identification device 114 to the particular dairy cow 104. By processing together those signals generated at or near the same time (e.g., using triangulation based on the distance information and a known location for each of the corresponding identification devices 114), controller 116 may determine a coordinate location (e.g., an (X,Y) location, an (X,Y,Z) location, or any other suitable coordinate location) of the particular dairy cow 104 within free stall pen 102 at each of the number of times during the time period.

At step 208, controller 116 may store the determined location information 128 associated with the particular dairy cow 104 (e.g., in memory module 120). At step 210, controller 116 may determine one or more movement parameters 130 associated with the particular dairy cow 104 (e.g., using estrus detection logic 124, described above) based on at least a portion of the stored location information 128 associated with the particular dairy cow 104. For example, the determined movement parameters 130 may include a stall standing

14

parameter 134, a stall lying parameter 136, an alley walking parameter 138, and alley lying parameter 140, an alley standing parameter 142, a watering parameter 144, a feeding parameter 146, a watering count 148, a feeding count 150, a mounting count 152, a mobility count 154, a distance traveled 156, a turn count 158, and/or a sign change count 160 (each of which are described above with respect to FIG. 1).

At step 212, controller 116 may determine whether the particular dairy cow 104 is likely to be in estrus (e.g., using estrus detection logic 124, described above) based on the one or more movement parameters 130 associated with the particular dairy cow 104. For example, controller 116 may determine whether the particular dairy cow 104 is likely to be in estrus by comparing a heat index for the particular dairy cow 104 with a baseline heat index. If the heat index for particular dairy cow 104 is greater than the baseline heat index by more than a predefined amount (e.g., 250%), controller 116 may determine that the particular dairy cow 104 is likely to be in estrus.

In embodiments in which the heat index corresponds to the product of an alley walking parameter 138 and a normalized mobility count 154 (e.g., $\text{heat index} = (\text{alley walking parameter}) \times (\text{mobility count/hour})$), an increase in heat index may be indicative of an increase in movement of the particular dairy cow 104 (which may be an indicator that the particular dairy cow 104 is in estrus). In embodiments in which the heat index corresponds to a function of stall standing parameter 134, stall lying parameter 136, alley walking parameter 138, alley lying parameter 140, ally standing parameter 142, watering parameter 144, feeding parameter 146, watering count 148, feeding count 150, mounting count 152, mobility count 154, distance traveled 156, turn count 158, and/or sign change count 160, an increase in certain activity of the particular dairy cow 104 (e.g., walking in walking lanes 108, pacing, and/or mounting other dairy cows 104) may be an indicator that the particular dairy cow 104 is in estrus.

As another example, controller 116 may determine whether the particular dairy cow 104 is likely to be in estrus by comparing a distance traveled 156 by the particular dairy cow 104 (e.g., a distance traveled during a particular time period, as described above) with a baseline distance traveled. If the distance traveled 156 by the particular dairy cow 104 is greater than the baseline distance traveled by more than a predefined amount (e.g., 250%), estrus detection logic 124 may determine that the particular dairy cow 104 is likely to be in estrus (as an increase in movement of the particular dairy cow 104 may be an indicator that the particular dairy cow 104 is in estrus).

As yet another example, controller 116 may determine whether the particular dairy cow 104 is likely to be in estrus by comparing a turn index (e.g., $\text{turn index} = (\text{turn count/hour}) \times (\text{sign change count/hour})$) for a particular dairy cow 104 with a baseline turn index. If the turn index for particular dairy cow 104 is greater than the baseline turn index by more than a predefined amount (e.g., 250%), controller 116 may determine that the particular dairy cow 104 is likely to be in estrus (as such an increase may be indicative of an increase in pacing by the particular dairy cow 104, which may be indicative of estrus).

If controller 116 determines at step 212 that the particular dairy cow 104 is likely to be in estrus, the method proceeds to step 214. Otherwise, the method returns to step 204. At step 214, controller 116 may confirm the determination that the particular dairy cow 104 is likely to be in estrus. For example, controller 116 may confirm the estrus determination by accessing stored information associated with the particular dairy cow 104 (e.g., stored in memory module 120) to deter-

15

mine if the particular dairy cow **104** is near the twenty-first day of her cycle. As an additional example, controller **116** may initiate the generation of a signal to be communicated to identification devices **114**, the signal causing identification devices **114** to increase the frequency with which the tag of the particular dairy cow **104** is read (e.g., from fifteen seconds to five seconds). As a result, updated location information **128** may be generated, movement parameters **130** may be recalculated based on that updated location information **128**, and a subsequent determination regarding whether the particular dairy cow **104** is likely to be in estrus may be made (in a manner substantially similar to that described above). As yet another example, controller **116** may access location information for other dairy cows **104** in free stall pen **102** to identify those other dairy cows **104** within a predefined distance of the particular dairy cow **104** in order to determine (1) whether any dairy cow **104** located near the particular dairy cow **104** is mounting the particular dairy cow **104** and/or (2) whether the particular dairy cow **104** is a member of a SAG (each of which is described above with regard to FIG. 1). At step **216**, the method ends.

Although the steps of method **200** have been described as being performed in a particular order, the present disclosure contemplates that the steps of method **200** may be performed in any suitable order, according to particular needs.

FIG. 3 illustrates an example method **300** for health monitoring, according to certain embodiments of the present disclosure. Although method **300** is described with regard to a particular dairy cow **104**, the present disclosure contemplates a substantially similar method being performed with regard to each of the plurality of dairy cows **104** in free stall pen **102**.

The method begins at step **302**. At step **304**, controller **116** receives signals generated by a number of the identification devices **114** positioned at various locations in and/or around free stall pen **102**. At step **306**, controller **116** processes the received signals (e.g., using RTL logic **122**, described above) to determine location information **128** associated with the particular dairy cow **104**. At step **308**, controller **116** may store the determined location information **128** associated with the particular dairy cow **104** (e.g., in memory module **120**). Steps **304-308** may be performed in a substantially similar manner to steps **204-208**, described above with regard to FIG. 2.

At step **310**, controller **116** may determine one or more movement parameters **130** associated with the particular dairy cow **104** (e.g., using health monitoring logic **126**, described above) based on at least a portion of the stored location information **128** associated with the particular dairy cow **104**. For example, the determined movement parameters may include a stall standing parameter **134**, a stall lying parameter **136**, an alley walking parameter **138**, an alley lying parameter **140**, an alley standing parameter **142**, a watering parameter **144**, a feeding parameter **146**, a watering count **148**, and/or feeding count **150** (each of which are described above with respect to FIG. 1).

At step **312**, controller **116** may determine whether the particular dairy cow **104** is likely unhealthy (e.g., using health monitoring logic **126**, described above) based on the one or more movement parameters **130** associated with the particular dairy cow **104**. For example, controller **116** may determine whether the particular dairy cow **104** is likely unhealthy by comparing a health index for the particular dairy cow **104** with a baseline health index. If the health index for particular dairy cow **104** is greater than the baseline health index by more than a predefined amount (e.g., 250%), controller **116** may determine that the particular dairy cow **116** is likely unhealthy. In embodiments in which the health index corre-

16

sponds to a function of a stall standing parameter **134**, a stall lying parameter **136**, an alley walking parameter **138**, an alley lying parameter **140**, an alley standing parameter **142**, a watering parameter **144**, a feeding parameter **146**, a watering count **148**, and/or a feeding count **150**, an increase in activity in certain portions of free stall pen **102** (e.g., an increase in the amount of time spent lying in walking alleys **108**) may be an indicator that the particular dairy cow **104** is unhealthy.

If controller **116** determines at step **312** that the particular dairy cow **104** is likely unhealthy, the method proceeds to step **314**. Otherwise, the method ends at step **316**. At step **314**, controller **116** may confirm the determination that the particular dairy cow **104** is likely unhealthy. For example, controller **116** may initiate the generation of a signal to be communicated to identification devices **114**, the signal causing identification devices **114** to increase the frequency with which the tag of the particular dairy cow **104** is read (e.g., from fifteen seconds to five seconds). As a result, updated location information **128** may be generated, movement parameters **130** may be recalculated based on that updated location information **128**, and a subsequent determination regarding whether the particular dairy cow **104** is likely unhealthy may be made (in a manner substantially similar to that described above). If the subsequent determination also indicates that the particular dairy cow **104** is likely unhealthy, the initial determination may be confirmed. At step **316**, the method ends.

Although the steps of method **300** have been described as being performed in a particular order, the present disclosure contemplates that the steps of method **300** may be performed in any suitable order, according to particular needs.

Although the present invention has been described with several embodiments, diverse changes, substitutions, variations, alterations, and modifications may be suggested to one skilled in the art, and it is intended that the invention encompass all such changes, substitutions, variations, alterations, and modifications as fall within the spirit and scope of the appended claims.

What is claimed is:

1. A system for estrus detection, comprising:

a plurality of identification devices positioned in a free stall pen;

one or more tags attachable to each of a plurality of dairy livestock in the free stall pen;

one or more memory modules that stores location information obtained from one or more of the plurality of identification devices and the one or more tags, the location information associated with a particular dairy livestock from the plurality of dairy livestock and comprising a plurality of coordinate locations of the particular dairy livestock within the free stall pen at each of a plurality of times during a time period including a first time and a second time, wherein the plurality of coordinate locations comprises at least a first (X, Y, Z) location of the particular dairy livestock at the first time and a second (X, Y, Z) location of the particular dairy livestock at the second time; and

one or more processors that:

determine, based on at least the first and second (X, Y, Z) locations, a turn index parameter indicating a number of times the particular dairy livestock reverses directions during the time period; and

determine whether the particular dairy livestock is likely to be in estrus based at least in part upon whether the determined turn index parameter is in excess of a baseline turn index parameter by more than a first predefined amount.

17

2. The system of claim 1, wherein the location information is generated by a real-time location system (RTLS) comprising the plurality of identification devices positioned in the free stall pen, the plurality of identification devices each operable to, at each of the plurality of times during the time period, generate a signal corresponding to the tag affixed to the particular dairy livestock.

3. The system of claim 2, wherein communication between the plurality of identification devices and the tag affixed to the particular dairy livestock is facilitated by ultra-wide band (UWB) technology.

4. The system of claim 2, wherein the RTLS is operable to determine the first (X,Y,Z) location of the particular dairy livestock within the free stall pen by triangulating the signals generated by at least three of the plurality of identification devices.

5. The system of claim 1, wherein:

determining a distance traveled parameter corresponding to a distance traveled by the particular dairy livestock during the time period; and

determining whether the particular dairy livestock is likely to be in estrus comprises determining whether the determined distance traveled parameter is in excess of a baseline distance traveled by more than a second predefined amount.

6. The system of claim 5, wherein the baseline distance traveled corresponds to an average distance traveled for a plurality of other dairy livestock in the free stall pen during a previous time period.

7. The system of claim 5, wherein the baseline distance traveled corresponds to a distance traveled by the particular dairy livestock during a previous time period.

8. The system of claim 1, wherein the one or more processors further determine, in response to determining that the particular dairy livestock is likely to be in estrus, whether the particular dairy livestock is a member of a sexually-active group.

9. The system of claim 8, wherein determining whether the particular dairy livestock is a member of a sexually-active group comprises:

accessing coordinate locations for each of a plurality of other dairy livestock in the free stall;

identifying one or more of the plurality of other dairy livestock that are within a predefined distance of the particular dairy livestock by comparing the coordinate locations for each of the plurality of other dairy livestock with a coordinate location of the particular dairy livestock; and

tracking the coordinate locations of the particular dairy livestock and the identified one or more of the plurality of other dairy livestock to determine if the identified one or more of the plurality of other dairy livestock remain within the predefined distance of the particular dairy livestock.

10. A system for estrus detection, comprising:

a plurality of identification devices positioned in a free stall pen;

one or more tags attachable to each of a plurality of dairy livestock in the free stall pen;

one or more memory modules that stores location information obtained from one or more of the plurality of identification devices and the one or more tags, the location information associated with a particular dairy livestock from the plurality of dairy livestock and comprising a plurality of coordinate locations of the particular dairy livestock within the free stall pen at each of a plurality of times during a time period including a first time and a

18

second time, wherein the plurality of coordinate locations comprises at least a first (X, Y, Z) location of the particular dairy livestock at the first time and a second (X, Y, Z) location of the particular dairy livestock at the second time; and

one or more processors that:

determine an alley walking parameter indicating a percentage of the time period that the particular dairy livestock was walking in a walking alley of the free stall pen; and

determine a mobility count parameter indicating a number of times during the time period that the particular dairy livestock moved greater than a predefined distance during a time interval within the time period; and

determine whether the particular dairy livestock is likely to be in estrus based at least in part upon whether a heat index for the particular dairy livestock is in excess of a baseline heat index by more than a predefined amount, the heat index for the particular dairy livestock corresponding to a multiplication product of the alley walking parameter and the mobility count parameter.

11. The system of claim 10, wherein the baseline heat index comprises an average heat index for a plurality of other dairy livestock in the free stall pen during a previous time period.

12. The system of claim 10, wherein the baseline heat index comprises a heat index for the particular dairy livestock during a previous time period.

13. The system of claim 10, wherein the baseline turn index parameter corresponds to an average number of times each of a plurality of other dairy livestock in the free stall pen reversed directions during a previous time period.

14. The system of claim 10, wherein the baseline turn index parameter corresponds to a number of times the particular dairy livestock reversed directions during a previous time period.

15. A system for estrus detection, comprising:

a plurality of identification devices positioned in a free stall pen;

one or more tags attachable to each of a plurality of dairy livestock in the free stall pen;

one or more memory modules that stores location information obtained from one or more of the plurality of identification devices and the one or more tags, the location information associated with a particular dairy livestock from the plurality of dairy livestock and comprising a plurality of coordinate locations of the particular dairy livestock within the free stall pen at each of a plurality of times during a time period including a first time and a second time, wherein the plurality of coordinate locations comprises at least a first (X, Y, Z) location of the particular dairy livestock at the first time and a second (X, Y, Z) location of the particular dairy livestock at the second time; and

one or more processors that:

determine a stall standing parameter indicating a percentage of the time period that the particular dairy livestock was standing in a stall of the free stall pen;

determine a stall lying parameter indicating a percentage of the time period that the particular dairy livestock was lying in the stall of the free stall pen;

determine an alley walking parameter indicating a percentage of the time period that the particular dairy livestock was walking in a walking alley of the free stall pen;

determine an alley lying parameter indicating a percentage of the time period that the particular dairy livestock was lying in the walking alley of the free stall pen;

determine an alley standing parameter indicating a percentage of the time period that the particular dairy livestock was standing stationary in the walking alley of the free stall pen;

determine a feeding parameter indicating a percentage of the time period that the particular dairy livestock was located within a predefined distance of a feed lane of the free stall pen; and

determine a watering parameter indicating a percentage of the time period that the particular dairy livestock was located within a predefined distance of a water trough of the free stall pen; and

determine whether the particular dairy livestock is likely to be in estrus based at least in part upon whether a heat index for the particular dairy livestock is in excess of a baseline heat index by more than a predefined amount, the heat index for the particular dairy livestock being a function of the stall standing parameter, the stall lying parameter, the alley walking parameter, the alley lying parameter, the alley standing parameter, the feeding parameter, and the watering parameter.

16. The system of claim **15**, wherein the baseline heat index comprises an average heat index for a plurality of other dairy livestock in the free stall during a previous time period.

17. The system of claim **15**, wherein the baseline heat index comprises a heat index for the particular dairy livestock during a previous time period.

* * * * *